

SAFETY DATA SHEET
METALBRYTE

Page 1
Issued: 01/08/2012
Revision No: 2

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: METALBRYTE

Product code: 708

Use of substance / preparation: Pc31: Polishes and wax blends

Company name: Fleetfield Chemical Co. Ltd
Unit 1, Norfolk Bridge Court,
Warren Street,
Attercliffe Road,
Sheffield, South Yorkshire
S4 7WT

United Kingdom

Tel: +44 (0) 114 2738999 Fax: +44 (0) 114 2738666

www.fleetfielddirect.co.uk sales@fleetfielddirect.co.uk

2. HAZARDS IDENTIFICATION

Classification Under CHIP: This product has no classification under chip

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: PETROLIUM DISTILLATE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
265-149-8	64742-47-8	Xn: R65; -: R66 Substance with a community workplace exposure limit	-	10-30%

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: Not applicable.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: No symptoms

4. FIRST AID MEASURES (ACTION)

Skin contact: No symptoms.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water to drink immediately Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If conscious, ensure

SAFETY DATA SHEET
METALBRYTE

the casualty sits or lies down. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Water. Water spray. Carbon dioxide.

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Protection of fire-fighters Wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Refer to section 8 of SDS for personal protection details.

Environmental precautions Do not discharge into drains or rivers.

Clean-up procedures: Absorb into dry earth or sand.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area.

Storage conditions: Store in cool, well ventilated area.

Suitable packaging: Polyethylene.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: PETROLEUM DISTILLATE

WEL (8 hr TWA): 1000 mg/m³ WEL

Engineering measures Ensure there is sufficient ventilation of the area.

Respiratory protection: Not required.

Hand protection: Gloves.

Eye protection: Safety glasses.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Off White

Odour: Characteristic odour

Viscosity: Highly viscous

Flash point°C: >93

Boiling Point: 100

pH: 7

Melting Point/range C: 0

Relative density: 1.09

VOC g/l: 150

SAFETY DATA SHEET

METALBRYTE

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid:

Materials to avoid:

Haz. decomp. products In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: Not Applicable

12. ECOLOGICAL INFORMATION

Mobility: Volatile.

Persistence and degradability biodegradable in part only.

Bioaccumulative potential Not Applicable.

13. DISPOSAL CONSIDERATIONS

Disposal of packaging Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

Transport Class: This product does not require a classification for transport.

15. REGULATORY INFORMATION

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

16: Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010

Phrases used in s.2 and 3: R65: Harmful: may cause lung damage if swallowed.
R66: Repeated exposure may cause skin dryness or cracking.

Legal Disclaimer: The above information is believed to be correct but does not purport to be an inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.